

# POWERCELL LOODLADER 24 V 15 A, 10100



Rating Input Voltage	100~120V or 220~240VAC, 50-60Hz			
Input Current	8A @ 100V input.			
Input power factor	0.7			
Charge voltage Limited	<b>10100</b>	36 V	48 V	60 V
	<b>29.4V±1%</b>	44.1V±1%	58.8V±1%	73.5V±1%
Bulk charge current	<b>10A~15A</b>	6A~10A	5A~8A	4A~6A
Float charge voltage	<b>27.6V±1%</b>	27.6V±1%	55.0V±1%	68.5V±1%
Operate Temp.	-20°C~40°C			
Cooling	Fan convection. Do not cover the charger.			
Charge principle	3 stages: CC-Bulk-Floating			
LED display	Bi-color LED indicator, "Red" for charging "Green" for full charged or idle. Red flashing for errors; "off" for no battery wired.			
Battery type	All types of 24V lead-acid batteries. (SLA, Gel, AGM, Wet....)			
Battery capacity	40-200Ah			
Size	223 x 126 x 71mm			
Output cable & plug	1.5 meter 2xAWG16#, SPT1 wire, DC plug type defined by user.			
Input AC plug	IEC60320-C14			
Enclosure	Aluminium casing, with Fan cover.			
Weight	1.2Kg			