


- Plug-in unit
  - Fixed output voltages
  - Thermal fuse in transformer
  - Standard version has bridge rectifier and capacitor
  - Exchangeable DC plugs
- 8711**
- Approvals:
    - Complies w. medical std EN 60601 (on request)
    - For updates: see [www.mascot.no](http://www.mascot.no)
- Plugg-inn enhet
  - Faste utgangsspenninger
  - Termosikring i transformator
  - Standardversjonen leveres med brolikeretter og kondensator
  - Utskiftbare DC plugger
- 8711**
- Godkjenninger:
    - Tilfredsst. medisinsk std EN 60601 (på forespørsel)
    - For oppdat.: se [www.mascot.no](http://www.mascot.no)



8511 not  
 8611 8311  
 only

Technical specifications	Tekniske data		8311	8511	8611	8711
Input voltage:	Inngangsspenning:	VAC	230 VAC +6/-10%, 50/60Hz			
Max. output power:	Maks. utgangseffekt:	W	2,5	6,5	8	10
Insulation class:	Isolasjonsklasse:		II			
Electrical safety standard:	Elektrisk sikkerhetsstandard:		EN 60950			
EMC standards	EMC standarder		EN 60065	EN 60065	EN 60065	EN 60065
• Emission:	• Emisjon:		EN 61000-6-3			
• Immunity:	• Immunitet:		EN 61000-6-1			
Dimensions excl. plug	Mål uten plugg:	LxWxH mm	75x45x49	95x51x57		100x51x63
Weight:	Vekt:	g	220	390	390	450

**Voltage versions - Spenningsversjoner**

VDC	Max. power (W) / Maks. effekt			
	8311	8511	8611	8711
1,5		1,9		
2	1,2			
3	1,5	3,5	2,0	6,0
4,5	2	4,5	4,0	7,0
6	2,5	5,5	6,0	8,0
7,5	2,5	5,5	6,5	8,5
9	2,5	6	7	10,0
10,5	2,5			10,0
12	2,5	6,5	7,5	10,0
15	2,5	6,5	8,0	10,0
18	2,5	6,5	7,5	10,0
21	2,5	6,5	8,0	10,0
24	2,5	6,5	8,0	10,0
28		6,5		10,0
30	2,5	6,5	8,0	
42		6,5	8,0	
48	2,5			

Individual data sheets are available at [www.mascot.com](http://www.mascot.com) / Individuelle dataark er tilgjengelige på [www.mascot.com](http://www.mascot.com)